Hubs

SMCUSBH7

EZ Connect™ 7 Port USB 2.0 Hub

OVERVIEW

The EZ Connect™ 7 Port USB 2.0 Hub is an easy to use solution for home and small business USB peripheral connectivity. This platform independent USB 2.0 hub allows high speed data rates up to 480 Mbps* with USB 2.0 connections (40X faster than USB 1.1) and is backwards compatible with USB 1.0 and USB 1.1 devices.

SMCUSBH7 provides seven downstream ports and one upstream port. Download ports are used to connect wide variety of USB enabled devices such as mice, keyboards, cameras, printers or external storages simultaneously. The upload port is used to connect to a host computer or another USB hub enabling up to 127 devices that can be daisy chained together by using multiple USB hubs.

SMCUSBH7 is also a Plug-and -Play device that works seamlessly with Microsoft Windows™ and Apple Macintosh™ for convenient compatibility and also allows USB devices to be connected or disconnected on the fly.

FEATURES	BENEFITS
7-Port USB 2.0 (Type A connection)	7-Ports allow connects of up to 7 USB enabled devices such as a mouse, keyboard, Digital cameras, printers, scanners, External Storage devices simultaneous
1-Port USB 2.0 (Type B connection)	Up to 127 USB devices can be connected by daisy chaining together with other USB hubs
High Speed USB 2.0 data transfer rate	When connected to USB 2.0 devices, it will allow up to 480 Mbps* data transfer rate
Support for USB 1.1 and USB 2.0	Includes legacy support for USB 1.X and 2.0 specifications allowing you to connect to older USB devices
Multiple PC and OS format support	Supports both Windows based PCs (98SE, ME, 2000, XP) and Mac (OS)

* Maximum transfer rate based on USB 2.0 specifications. Actual throughput may vary.

SMC Networks

TECHNICAL SPECIFICATIONS SMCUSBH7

STANDARDS
- USB Specifications 2.0
- USB Specifications 1.1
- USB Specifications 1.0
- OHCI (Open Host Controller Interface)
- EHCI (Enhanced Host Controller Interface)

INTERFACE
- 7 Downstream USB Type B Port
- 1 Upstream USB Type A Port

LEDS
- Power
- Port Status/ Activity

POWER REQUIREMENTS
- Input: 100-240V ~ 50/60Hz 0.3A
- Output: 5V 2.5A

SUPPLIED CURRENT FOR SELF-POWERED MODE
- 500mA per port

TEMPERATURE
- Operating: 32° to 104° F / 0° to 40° C
- Storage: 14° to 176° F / -10° to 80° C

HUMIDITY
- 5% to 95% (non condensing)

COMPLIANCES
- FCC Class B
- CE
- VCCI
- UL

DIMENSIONS
- 3.94 x 2.36 x .95 in
- 10 x 6 x 2.5 cm

WEIGHT
- 3.81oz/ 108g

Contact

North America
38 Tesla
Irvine, CA 92618
1-800-SMC-4YOU
24/7 Technical Support

Europe/ Africa
Fructuos Gelabert 6-8
08970 Sant Joan Despí
Barcelona, Spain

Check www.smc.com for your local country contact information